products

Overhead Door launches OHD Anywhere

In January, Overhead Door introduced OHD Anywhere, its new Wi-Fi-enabled garage door controller that allows homeowners to remotely monitor and safely control their Overhead Door garage door openers from a compatible smart device.

If the garage door is activated from the owner's smart device, an audible and visual warning will alert those around the door that it is about to move. The system is UL 325 compliant.

OHD Anywhere comes with a door position sensor that attaches to the garage door. The sensor relays any change in its position to the control module, allowing the homeowner to know whether the door is open or closed via a signal to their smart device.

Unlike remote access systems that are built into the powerhead, OHD Anywhere offers increased security by alerting a homeowner

even if the garage door is opened or closed manually. One sensor comes standard with the unit; additional sensors can be purchased to monitor up to three doors.

Check www.overheaddoor.com for a list of compatible openers and smart devices. www.overheaddoor.com ■



Genie launches Aladdin Connect

In December, Genie unveiled its new garage door controller, Aladdin Connect, which gives the ability to remotely monitor and change the open/close position of a garage door from a smart device.

When activated the LIL 325-compliant system provides an audible

When activated, the UL 325-compliant system provides an audible and visual signal that the door is about to move. The Wi-Fi-enabled control module works with a door position sensor that attaches to the

garage door, relaying any change in its position, whether operated manually or via the opener.

"Since Aladdin Connect works for Genie openers and other brands as well, it creates many opportunities for our dealers," said Dave Osso, brand manager. "Even if a homeowner doesn't need a new door or opener, many will find the features of Aladdin Connect appealing and

provide dealers sales opportunities they otherwise would not have."

An up-to-date list of compatible openers and smart devices is at the Genie website.

www.geniecompany.com/aladdinconnect

LiftMaster adds video viewing capability

In January, LiftMaster announced a new integration with Nest, making it possible for customers to access Nest Cam video through the LiftMaster MyQ app. With a Nest Cam in the garage, users can now use their smartphones to view a video feed of what's happening in the garage the moment the garage door is activated.



The system requires placing a Nest Cam in the garage and linking the MyQ and Nest Cam apps. With the MyQ app, consumers can:

- Access both MyQ and Nest Cam from anywhere within one smartphone app.
- Monitor home activity every time the garage door opens or closes.
- Get MyQ alerts when Nest Cam detects motion wherever the Nest Cam is placed.
- See time-lapsed video clips and event history with a special subscription.

 www.liftmaster.com


Clopay showcases new designs at 2016 Builders' Show

In January at the 2016 International Builders' Show in Las Vegas, Clopay debuted a new panel design and showcased its Modern Steel collection, which includes garage doors that feature clean lines, large expanses of glass, and custom colors.

Clopay Modern Steel Collection doors have a three-layer insulated construction with optional

Intellicore polyurethane foam insulation for an 18.4 R-value. The collection includes Clopay's WindCode Storm-Ready reinforcement for coastal and high-wind regions as well as grooved and flush panel designs.

In addition, Clopay debuted a new custom panel design for its Avante Collection, demonstrating how the stiles and rails can be adjusted to add visual interest and control the amount of daylight that enters the garage. The new models will be available in the spring of 2016. www.clopay.com



products



Rytec announces new freezer door

In 2015, Rytec introduced its Turbo-Slide insulated freezer door, calling it "the fastest solid panel door on the market." It delivers speeds up to 120" per second for energy-loss protection and to enable rapid traffic flow.

The Turbo-Slide includes proprietary Flex-Panel technology for reduced downtime from collisions. Totally closed-cell EVA foam panels produce R-values up to 40. The door is available in both single-panel and bi-part designs for high-cycle applications where productivity and energy efficiency are top priorities. www.rytecdoors.com

Garaga adds two new garage door models

In February, Garaga added the Vog and Prestige models, two new garage door model patterns. The designs were developed to coordinate with Novatech's entry-door models.

The Vog model features horizontal, 40" long, V-shaped grooves that are embossed on each section. The Prestige

model has rectangular embossed patterns (40.5" x 15") with contours that are highlighted with fine details. The new models are available on Garaga's Standard+ 1-3/4" insulated door that offers nine other model patterns.

"Consulting with consumers and our network of dealers uncovered that homeowners are increasingly looking to perfectly coordinate the design of their entry door with that of their garage door," said Maxime Gendreau, director of marketing. "The trend is the same for the windows that can be added to the garage door and the main entry door." www.garaga.com





C.H.I. expands Accents offerings

In January, C.H.I. introduced Accents Woodtones that feature the "highest resolution finishes available," achieving the look of a handcrafted wood door at a lower cost. Woodtones' woodgrain does not repeat its pattern throughout

the horizontal and vertical grains and flows through section joints, thus accentuating the recessed edge of the raised panel design.

Accents Woodtones is available on raised panel models 2216/4216 and 2283/4283 in light oak, dark oak, cedar, and mahogany. Each model can be customized with insulation, window inserts, and designer glass currently offered in raised panel doors. www.chiohd.com

Entrematic adds color and layer options



In January, Entrematic added two new colors and single- and double-layer door options to its Amarr Lincoln and Hillcrest collections. The Amarr Lincoln LI3000 and Hillcrest HI3000 insulated residential garage doors are now available in two new solid colors, almond and terratone, plus three bidirectional woodgrain colors: golden oak, walnut, and mahogany.

The Lincoln traditional and Hillcrest carriage house collections both feature 2"-thick steel doors with a polystyrene insulation option. Each collection is available in nine colors and a variety of DecraTrim and DecraGlass window offerings. www.entrematic.us

Genie announces timed close feature

In December, Genie announced the addition of timed close functionality to its standard and heavy-duty commercial operators. This feature allows automatic closure of a commercial door after a configured time delay expires. The timed close delay can easily be configured through the operator LCD display from two

seconds to five minutes.

The software and hardware designs of the commercial operators allow a full-featured Timer Close Module to be installed for installations requiring advanced timer features. This includes the timer hold input, pre-close warning output, and auxiliary open input. Genie commercial operator expansion modules are plug-and-play, so the module's menu options are automatically added to the menu without any additional configuration.

www.geniecompany.com



Haas introduces charcoal color

In March, Haas Door added charcoal to its lineup of color options. This

new 18th color features a low-gloss finish and is now available in all residential and commercial insulated steel doors from 1-3/8" to 3" thick.

Charcoal is also available in the RA360 and CA220 aluminum full-view models and in the American Tradition Series in both base and overlay colors for all carriage house door models. www.haasdoor.com

C.H.I. adds black to color options

In December, C.H.I. added black as a new standard color for its 2" residential urethane doors. It is now available on raised panel models 2216/4216, flush model 2217, and stamped carriage house models 5216/5916.

The black color is available with only a oneweek lead time and costs up to 30 percent less than powder-coated black doors. www.chiohd.com



continued on page 12



Re-Source adds new line of magnetic decorative hardware

In February, Re-Source Industries added the Traditional Magnetic line of decorative hardware to its carriage house hardware line.

Made of lightweight, rust-resistant black ABS plastic with UV protection, this line features a textured finish with the realistic appearance of hammered iron. The



product line includes hinges and handle sets with built-in clavo looks.

The magnetic hardware won't rust, chip, or fade. It has been UV tested for long-term weatherability and installs in seconds without any tools. The neodymium magnets maintain 99 percent of their strength for 10 years.

www.re-sourceind.com

Amarr model achieves wind load approval

In February, Entrematic announced that its Amarr Oak Summit OS3200 garage door is wind-load approved for Miami-Dade and Florida impact. The OS3200 is a 24-gauge 2"-thick impact-resistant garage door, while the Oak Summit collection features four stamped steel carriage house designs. www.entrematic.us



Re-Source adds Marantec and Guardian accessories

In February, Re-Source Industries announced the addition of Guardian and Marantec radios, receivers, battery backups, transmitters, photo eyes, logic and power boards, and more to its extensive inventory of radio controls and operator replacement parts.

The Re-Source line of garage door opener accessories also includes the LiftMaster, Genie, Linear, Manaras, MultiCode, and MegaCode brands. www.re-sourceind.com ■

Wayne Dalton earns ICC Evaluation Service listing

In January, Wayne Dalton announced that its Model 800C ThermoTite insulated rolling steel door now has an IECC air infiltration option that recently received a building product listing from ICC Evaluation Service (ICC-ES). This indicates that the 800C with IECC option meets specific consensus standards requirements in the I-codes.

Building officials, architects, contractors, specifiers, and others utilize ICC-ES Building Product Listings to provide a basis for using or approving product in construction projects under the International Building Code.

ICC-ES thoroughly examined Wayne Dalton's product information, test reports, calculations, quality control methods, and other factors to ensure the product is compliant with the specific consensus standards.

www.wayne-dalton.com

Overhead Door rolling door earns ICC Evaluation Service listing

In January, Overhead Door announced that its Stormtite Model 625 rolling steel door had earned the highest quality of product review through certification by the ICC Evaluation Service (ICC-ES).

The ICC-ES listing provides assurance that the Stormtite Model 625 meets the International Energy Conservation Code (IECC) consensus standards for air infiltration through test reports, calculations, examination of product information, and quality control methods.

Building departments use evaluation reports as a basis for approving products. The Overhead Door listing is available at www.icc-es.org. www.overheaddoor.com

Door E-Z controllers meet new UL 325 requirements



In December, Cinch Systems announced that the CeLAN Door-EZ door and security gate controls and modules are compliant with new UL 325 requirements that became effective on Jan. 12, 2016.

The new UL 325 standard requires that commercial door and gate operators must monitor safety devices such as photo sensors and/or sensing edges on every operation cycle. They must also have a minimum of two independent means of entrapment protection where the risk of entrapment or obstruction exists.

The Door-EZ is a microprocessor-based control system that can be used as a stand-alone door/gate controller or in a multi-door/gate system with a Cinch control panel. www.cinchsystems.com

Schweiss announces interlocking insulated panels

In February, Schweiss Doors announced its interlocking insulated panels that can be installed quickly as a cost-effective solution for door owners, contractors, and installers.

The attractive interior lightweight durable panels with interlocking edges fasten to the exterior of the doorframe, reducing installation time and providing a fully insulated thermal barrier.

The lightweight insulated panels are available in 1-3/8", 2-3/8", and 3-3/8" thicknesses. Standard panel width is 4' and can be ordered in multiple lengths. www.bifold.com



